

PRODUCT SPECIFICATIONS

Rotating D-Ring Anchor

#7393

Features

- Anchor Rotates 360° and pivots 180° side-to-side
- Permanent and Temporary installations supported for Steel
- Anchor is rated up to 10,000 lbs Tensile Strength
- User-supplied fasteners required; Grade 8 recommended

Material Specifications

Connector D-ring : Zinc Plated Alloy Steel; 5,000 lbs Min

Performance Specifications

Tensile Strength: 5,000 lbs Min

ANSI User Capacity: 130 to 310 lbs Max.

OSHA User Capacity: 130 to 425 lbs Max.



Relevant Standards

OSHA: 1910.66 and 1926.502

ANSI: Z359.1-2007

Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.

FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 www.falltech.com

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THIS INFORMATION HOWEVER, IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ AND UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.