



AV-2PBP

Pneumatic HEPA Vacuums

Pneumatic powered vacuums are ideal for working in wet environments or where long lengths of vacuum hose are required. Air motors require no maintenance and contain no moving parts. A built-in pressure relief valve restricts water lift to 160" to prevent tank collapse. An on/off flow valve and pressure gauge are provided. Spark-free air motor.



AV-15P



AV-5P

Specifications

- Inlet Pressure: 80 psi with 1/2" I.D. hose
- Inlet Flow: 70 cfm required
- Vacuum Pressure: 250" water lift maximum, adjusted to 160" water lift with relief valve
- Vacuum Flow: 100 - 170 cfm based on inlet pressure
- Noise Level: 75dbA @ 90 psi inlet pressure
- Tank: Stainless Steel

Model No.	Description
AV-2P	2 gallon recovery, pneumatic motor, stainless steel tank, complete with wand, filters, and accessories
AV-5P	5 gallon recovery, pneumatic motor, stainless steel tank, wand, accessory tools, and filters
AV-15P	15 gallon recovery, pneumatic motor, stainless steel tank, cart, wand, accessory tools, and filters
AV-55P	55 gallon drum lid assembly with HEPA filter, 1.5" hose connection, and pneumatic motor
Back-Pack Pneumatic Model	
AV-2PBP	2 gallon, pneumatic motor, stainless steel vacuum with back pack frame

See Page 69 for Replacement Bags, Filters and Accessories

Conductive Pneumatic HEPA Vacuums Safely Remove Potential Static Charge Build-up

- Pneumatic spark free vacuum motor
- All aluminum non-sparking tools and 2-piece aluminum wand
- 10 ft., 1.5" Conductive Vacuum hose with cuffs (grounds to tank)
- Motor head has grounding wire attached to the recovery can
- 25 ft. ground wire is attached to the vacuum recovery can to attach to a grounded external device for static removal

Specifications

- Inlet Pressure: 1/2" I.D. hose - 80 psi
- Inlet Flow: 70 cfm required
- Vacuum Pressure: 250" water lift maximum, adjusted to 160" water lift with relief valve
- Vacuum Flow: 100 - 170 cfm based on inlet pressure
- Noise Level: 75dbA @ 90 psi inlet pressure



AV-15P-CND



AV-55DD



AV-55P-CND

Note: AV-55P-CND is supplied with all ground wires connected, conductive hose, steel drum and a 55 gallon drum dolly

Model No.	Description
AV-2P-CND	2 gallon recovery, pneumatic motor, stainless steel tank, complete with wand, filters, accessory tools and ground wires
AV-5P-CND	5 gallon recovery, pneumatic motor, stainless steel tank, wand, filters, accessory tools and ground wires
AV-15P-CND	15 gallon recovery, pneumatic motor, stainless steel tank, cart, wand, filter accessory tools and ground wires
AV-55P-CND	55 gallon drum lid assembly with HEPA filter, 1.5" conductive 10ft hose, pneumatic motor, steel 55 gallon drum, drum dolly, filters, accessory tools and ground wires
AV-55DL	Drum lid includes 1.5" goose neck adapter (order motor, filters, and hoses separately)
AV-55DD	Drum Dolly - 55 gallon

See Page 69 for Replacement Bags, Filters and Accessories

[Air Systems International AV-15P Pneumatic HEPA Vacuum](#)
[Air Systems International AV-15P-CND Pneumatic HEPA Vacuum](#)
[Air Systems International AV-2P Pneumatic HEPA Vacuum](#)
[Air Systems International AV-2PBP Pneumatic HEPA Vacuum](#)
[Air Systems International AV-2P-CND Pneumatic HEPA Vacuum](#)
[Air Systems International AV-55P Pneumatic HEPA Vacuum](#)
[Air Systems International AV-55P-CND CND Pneumatic HEPA Vacuum](#)
[Air Systems International AV-5P Pneumatic HEPA Vacuum](#)
[Air Systems International AV-5P-CND Pneumatic HEPA Vacuum](#)